


RAYFORM DURAÇÓRE

www.essentialpro.net | 800-331-8811

Innovative technology allows for virtually "warp free" durability.



Rayform DuraCore Dieboard

TECHNICAL INFORMATION

General Properties:

- Virtually "Warp Free"
- Outstanding stability (less than .005")
- Outstanding rule holding strength
- Re-knife's easily with no slot expansion
- Laser cuts at 45"/min or higher
- Consistent kerf width's
- Impervious to moisture
- Withstands high temperatures
- Sold by the piece

Linear Expansion	% Chg	<.005
Density	g / cc	1.38
Thickness Variation	inches	+/005
Squareness	inches	.25
Warp / Twist	inches	< .005
Moisture Content	%	< .3
Water Absorption (24 hr)	%	2%
Flexural Strength	psi	32,000
Flexural Modulus	psi	2,000,000
Compressive Strength	psi	40,000
Compressive Deflection	@7000 psi	.03 in
Internal Bond Strength	pounds	1,100
Impact Strength (w grain)	ft. lbs. / in.	1.2
Impact Strength (x grain)	ft. lbs. / in.	1.2
Rockwell Hardness	M-Scale	110
Laser Cutting Speed	in. / min.	> 45 in.

Notes: Rayform DuraCore Dieboards are sold by the piece. Contact your Essential Products Representative for a sample.

rotary boards

Rayform Rotary TruLine Rotary Exact Rotary Maple Rotary Beech Rotary

flat boards

Rayform DuraCore Rayform PolyCore Rayform DuraPly Exact Board Premium Maple Standard Maple Premium Euro Birch Premium Coated Euro Birch

specialty products

EP CounterPlate DuraBlanker One Step Perma-Bond PowerPlate EP Channel Bits

